

Ultrasonic Wind Sensor uSonic-2 Wind

previously USA-2



- Cost efficient sensor for precise measurement of horizontal wind
- No moving parts, no maintenance
- Measuring range up to 216 km/h
- Robust stainless steel construction
- Ice protection by efficient sensor heating
- Reliable long term operation
- Analogue data output
- Graphical user interface



Ultrasonic Wind Sensor uSonic-2 Wind

previously USA-2

Typical Applications

- Meteorological systems
- Routine observation of wind parameters
- Installation in severe site conditions
- Ice protection for mountain sites
- Long term unattended operation
- Meteorological networks
- Research stations
- Industrial sites
- Airports
- Marine and offshore platforms
- Wind energy
- Sport events


The Ultrasonic Anemometer **uSonic-2 Wind** is a 2D wind sensor for standard meteorological applications. It has proven reliable operation in all weather types, outstanding flexibility, high rated system performance and user friendly operation in widespread applications. It delivers raw or mean values of wind components x and y including acoustic temperature or horizontal wind speed and wind direction via serial interface RS422 / RS485 or as analogue output.

For reliable operation in adverse conditions icing can be prevented by an efficient sensor head heating. The operation of the heating is controlled and monitored by the sensor electronic.

The sensor head design had been optimized by comprehensive wind tunnel tests and which assures precise wind data for the whole measuring range.

Average time / number	1 ... 3600 s / 1 ... 65365 samples
Sampling rate	0.1... 40/50 Hz
Ranges	0 ... 45 / 60 m/s, -40 ... +70 C, 5 ... 100 %
Accuracy (max. dev.) Wind speed / wind direction	0.1 m/s or 2 % / 2 at 5 m/s
Resolution	0.01 m/s, 0.1 ,0.01 K
Azimuth alignment	0 ... 359 , adjustable
Output data set	x, y, T or vel, dir, T
Averaging method	scalar, vectorial
Output protocols	standard, checksum, NMEA
Data output	async, polling, time synchronized
Internal memory	15300 data sets
Power supply	9 ... 36 VDC / 3 W
Sensor head heating (option)	24 VDC / 55 W / 110 W on / off / auto, monitored
Analogue output	4 x 0-20/4-20 mA and 2 x 0-5/ 2.5/ 5 VDC 12 bit, range adjustable
Serial interface	RS422, RS485 (300 ... 115200), ASCII
Mounting	stud Ø (outer) 34 mm adapters available Ø (inner) 55 mm

User interface (GUI)



Graphic output



Mechanical drawing

